



Data sheet - LRS 1

LRS 1, 60 m³/h, European motor

LRS 1, 60 m³/h, European motor

LRS 1



Similar Image

Technical Data

LRS 1, 60 m³/h, European motor

Dimensions (L x W x H)	856 x 331 x 685 mm
Flange (in)	DN 63 ISO-KF
Flange (out)	DN 40 ISO-KF
Lubricant filling	7.7 l
Mains requirement	3 Phases 200/240 V or 380/415 V, 50 Hz; 3 Phases 200/240 V or 380/480 V, 60 Hz
Motor	Japanese motor
Operating fluid	A120
Power consumption	4.1 kW
Pumping speed at 1 hPa, 50 Hz	265 m ³ /h
Pumping speed at 1 hPa, 60 Hz	320 m ³ /h
Pumping speed at 50 Hz	300 m ³ /h
Pumping speed at 60 Hz	360 m ³ /h
Type	Roots pumping station
Ultimate pressure	2 · 10 ⁻⁴ hPa
Version	without frame
Weight	186 kg

Order number

**LDHKNNNNNN
E**

**Vacuum solutions
from a single source**

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

**Complete range
of products**

From a single component to complex systems:
We are the only supplier of vacuum technology
that provides a complete product portfolio.

**Competence in
theory and practice**

Benefit from our know-how and our portfolio of training
opportunities! We support you with your plant layout
and provide first-class on-site service worldwide.

**Are you looking for a
perfect vacuum solution?
Please contact us:**

Pfeiffer Vacuum GmbH
Headquarters · Germany
T +49 6441 802-0
info@pfeiffer-vacuum.de
www.pfeiffer-vacuum.com