



Data sheet · LRS 3, Pascal 2063 SD + OME 40 S, Roots 600

LRS 3, Pascal 2063 SD + OME 40 S,
Roots 600, elec. box, European motor

Data sheet - LRS 3, Pascal 2063 SD + OME 40 S, Roots 600

LRS 3, Pascal 2063 SD + OME 40 S, Roots 600, elec. box, European motor

**LRS 3,
Pascal
2063 SD +
OME 40 S,
Roots 600**



Similar Image

Technical Data

**LRS 3, Pascal
2063 SD + OME
40 S, Roots
600, elec. box,
European
motor**

Dimensions (L x W x H)	1320 x 400 x 1090 mm
Flange (in)	DN 100 ISO-KF
Flange (out)	DN 40 ISO-KF
Lubricant filling	7.7 l
Mains requirement	3 Phases 180/250 V or 360/480 V, 50 Hz-60 Hz
Motor	US motor
Operating fluid	A120
Power consumption	4.1 kW
Pumping speed at 1 hPa, 50 Hz	400 m ³ /h
Pumping speed at 1 hPa, 60 Hz	490 m ³ /h
Pumping speed at 50 Hz	600 m ³ /h
Pumping speed at 60 Hz	720 m ³ /h
Type	Roots pumping station
Ultimate pressure	2 · 10 ⁻⁴ hPa
Version	with frame and electronics
Weight	238 kg

Order number

**LFQANNNNC
4E**

**Vacuum solutions
from a single source**

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

**Complete range
of products**

From a single component to complex systems:
We are the only supplier of vacuum technology
that provides a complete product portfolio.

**Competence in
theory and practice**

Benefit from our know-how and our portfolio of training
opportunities! We support you with your plant layout
and provide first-class on-site service worldwide.

**Are you looking for a
perfect vacuum solution?
Please contact us:**

Pfeiffer Vacuum GmbH
Headquarters · Germany
T +49 6441 802-0
info@pfeiffer-vacuum.de
www.pfeiffer-vacuum.com